

X660SJ

COMPACT CRAWLER

BOOM LIFT



KEY SPECS

Platform Height

65-ft 7-in / 20-m

Horizontal Outreach

39-ft / 11.9-m

Working Height

71-ft 7-in / 21.81-m

Platform Capacity

500-lb / 227-kg

KEY FEATURES

- Best in class 500-lb unrestricted platform capacity, with SkyGuard SkyLine™ standard.
- Environmentally friendly with standard AC powered boom functions with diesel, optional bi-energy or optional lithium-ion electrical system for emission-free operation.
- Transport with ease by a forklift or crane with forklift pockets and lifting eyes, and fits through double doorway.
- Enhance efficiency with unique "Go Home" and "Go Back to Work" functions for ease of returning to stowed or recorded work position.

ACCESSORIES

- Black Deep-Tread Tracks
- Outrigger Sliding Pads
- Platform, Single-Person 31 x 24-in

STANDARD SPECIFICATIONS

Performance

Platform Height	65-ft 7-in / 20-m
Working Height	71-ft 7-in / 21.81-m
Max Working Horizontal Outreach	39-ft / 11.9-m
Platform Capacity	500-lb / 227-kg
Swing	360 Degrees Non-continuous
Jib (Range of Articulation)	89 Degrees (0/-89)
Travel Speed (Diesel)	1.2 mph / 2.0 km/h
Travel Speed (Lithium Ion & Bi-Energy)	1.6 mph / 2.6 km/h
Max Front Approach Angle:	19 Degrees
Max Rear Approach Angle:	19 Degrees
Leveling Capability	15 Degrees
Gradeability	40%
Ground Bearing Pressure (Tracks)	79.7 psi / 5.6 km/cm2
Ground Bearing Pressure (Outriggers)	9.08 psi / .63 kg/cm2

Outrigger Footprint (From Outer Edge):

Total Stabilization Area	14-ft 1-in x 13-ft 4-in / 4.27-m x 4.08-m
Reduced Stabilization Area	18-ft 10-in x 7-ft 11in / 5.73-m x 2.41-m
Weight (Diesel & Bi-Energy)*	7,385-lb / 3,350-kg
Weight (Lithium Ion)*	7,275-lb / 3,300-kg

*Certain options or country standards increase weight.

Power

Diesel Engine	Diesel Kubota Z602 14.5 HP / 10.8 kW
Fuel Tank Capacity (Diesel)	7.4 gal. / 28-L
Electric-motor	
Optional: 51.4V 120 Ah Lithium Ion Battery	
Optional: Bi-Energy	

Tracks

Standard	Non-marking Tracks
----------	--------------------

Hydraulic System

Capacity	10.6 gal / 40 L
----------	-----------------

STANDARD FEATURES

- 110V AC Receptacle in Platform 58 x 30-in
- 360 Degree Non-Continuous Swing
- 5-ft Articulating Jib
- AC Motor for Indoor Operation
- Air/Water Line to Platform
- Electronic Controls with One-Touch Outrigger Deployment
- Emergency Lowering Pump
- Flashing Amber Beacon
- Fork Lift Pockets
- Lifting Eyes
- Load Sensing System
- Non-Marking Tracks
- Powered Track Widening
- Proportional Controls
- Removable Aluminum Platform Dual Side Entry
- Removable Controller
- SkyGuard SkyLine™
- Synthetic Biodegradable Hydraulic Oil
- Telematics-Ready Harness
- Tie Down Lugs

