

JLG Industries, Inc. 1 JLG Drive McConnellsburg, PA 17233-9533

BOOM LIFT and TRAILER MOUNTED BOOM LIFTS **Annual Machine Inspection Report**

JLG Account Holder Name & Address

Product Owner/User Name & Address

Owner User

Serial Number:	Customer No. :
Machine Model:	

Hourmeter Reading:

Previous Inspection Date _____

ANNUAL MACHINE The Owner must perform an Annual Machine Inspection of this machine no later than 13 months from the date of the prior Annual Machine Inspection. This Annual Machine Inspection is to be performed by a mechanic qualified on the specific make and model of aerial work platform.

Check each item below. (Refer to Operators & Safety, Service & Maintenance Manuals for specific information regarding inspection procedures and criteria.) Indicate in the appropriate space as each item has been performed. If the item is found to be not acceptable, describe each discrepancy in the comments space at the bottom of the form. Use additional paper if necessary. Immediate action must be taken to correct all discrepancies. The Owner shall not place the machine in service until all discrepancies have been corrected.

Y=Yes (Passed) N=No (Failed) C=Corrected NA=Not Applicable Y N C NA	$Y = Yes$ (Passed) $N = No$ (Failed) $C = Corrected$ $NA = Not Applicable$ $Y \mid N \mid C \mid NA$	Y=Yes (Passed) N=No (Failed) C=Corrected NA=Not Applicable Y N C NA		
FUNCTIONS & CONTROLS	BOOM ASSEMBLY (continued)	HYDRAULIC/ELECTRICAL SYSTEM (continued)		
1. All controls return to neutral/off position when released.	 Inspect all cylinder pins, pivot pins, attaching & retention hardware for damage, distortion & excessive wear. 	2. All areas around hydraulic components (pump, oil lines, reservoir) free of oil, no evidence of leaks.		
 Detents properly lock controls in neutral/off position. Check condi- tion of control enclosures & protective boots/guards. 	TURNTABLE	3. Hydraulic oil free of contaminants, hydraulic filter clean.		
3. Footswitch operates properly. (shuts off function when released)	1. Hood doors open & latch properly.	4. Hydraulic level in tank & torque hubs correct.		
4. Emergency stop switches at the ground & platform control stations	2. Hood props in place, secure and functioning properly.	5. Hydraulic tank cap tight & vent open.		
arrest all platform movement.	3. Turntable bearing, swing drive & gear secure and undamaged,	6. All hydraulic fittings & lines secure, free of damage, chafing & leaks.		
5. All function & speed cut-outs operate properly.	properly lubricated. No missing bearing bolts or signs of looseness.	7. All electrical connections tight, no corrosion or abrasions.		
 Manual descent system and/or auxilillary power system operates properly. 	4. Check swing bearing bolt tolerance per the Service & Maintenance Manual.	8. Instruments, switches, gauges, horn & lights operate properly.		
7. Tower boom sychronization and sequence system operates prop-	5. Turntable lock secure, undamaged & operable. (If equipped)	9. Pump & motor secure, undamaged & free of leaks.		
erly. (HA & A models)	CHASSIS	10. All hydraulic pressures properly adjusted.		
8. Capacity indicator system operates properly.	1. Wheel rim nuts torqued properly.	MANUALS & DECALS		
9. Brakes operate properly. (swing & drive)	2. Proper tires installed.	ANSI/SIA Manual of Responsibilities in manual storage box. Operators & Safety Manual in manual storage box.		
10. Machine controls operate properly at platform & ground control sta-	3. Tires free of gouges and excessive wear, no cords showing. If	3. AEM Handbook in manual storage box.		
tions. (lift, swing, drive, telescope, etc.)	pneumatic, properly inflated. Tire bead properly seated around rim.	4. Capacity decals installed & legible at both platform & ground sta-		
PLATFORM ASSEMBLY	 Oscillating axle operates properly, locks in place when turntable swings to side. 	tions.		
1. Platform installed & secure. Mounting hardware free of damage & secure. Gate opens & latches properly.	5. Outrigger/extendible axles operate properly. Interlocks function	5. All safety & instructional decals installed, secure & legible. GENERAL		
2. Platform guardrails and floor in place, secure and undamaged.	properly.			
3. Lanyard anchorage points secure, undamaged & labeled.		Lift is free of unauthorized modifications or additions.		
BOOM ASSEMBLY	1. Engine idle, throttle & RPM set properly.	2. Paint and overall appearance.		
1. Boom sections free of damage, distortion & excessive wear.	2. Battery fluid levels correct.	3. Applicable Safety Bulletins completed.		
2. All nuts, bolts, pins, shafts, shields, bearings, wear pads, locking	3. Battery charger scrolls through diagnostics when plugged in.	4. Inspect general structural condition including all welds.		
devices, checked for proper installation, no excessive wear, cracks	4. Batteries accept charge.	5. Grease and lubricate per Service & Maintenance Manual.		
or distortion.	5. Air & fuel filter clean.	6. Drive & operate machine to test all machine functions.		
 Inspect all sheaves, sheave pins and bearings for proper installa- tion, secure, no excessive wear, cracks or distortion. 	6. Fuel, coolant and engine oil level correct.	 If ownership has changed, complete attached Owner Update form and return to JLG. 		
4. Boom chains and cables are free of damage, properly installed,	7. Fuel cap tight & vent open.	Comments:		
properly torqued & properly lubricated.	8. Exhaust system free of leaks.	comments.		
5. Powertrack is free of damage, distortion & excessive wear. Cables/	HYDRAULIC/ELECTRICAL SYSTEM			
hoses are properly routed, no chafing or leaks.	1. All cylinders free of damage, no evidence of leaks.			

The undersigned certifies that this machine has been inspected, per each area of inspection, and any and all discrepancies have been brought to the attention of the Owner/User, and that all discrepancies have been corrected prior to any further use of this machine.

Printed Signature