

PRODUCT SAFETY & RELIABILITY DEPARTMENT

P: 877.JLG.SAFE

E: PRODUCTSAFETY@JLG.COM



Attn: Safety Manager or Service Manager

Subject: Transferring to a Structure from the Platforms of JLG Products While Elevated

Pursuant to inquiries for information regarding the noted subject, the JLG Industries, Inc. Product Safety & Reliability Department submits the following:

JLG Industries, Inc. requires owner, user, operator, lessor and lessee compliance with all applicable regulations (employer, local, state, and national) pertaining to the utilization of Mobile Elevated Work Platforms (MEWP). Be aware that some jurisdictions do not allow for exiting of MEWPS at height under any circumstances.

When transfer is necessary, enter/exit through the gate only with the platform within 1 foot (0.3 m) of a safe and secure structure. 100% tie-off is also required in this situation utilizing two lanyards. One lanyard must be attached to the platform with the second lanyard attached to the structure prior to transfer. The lanyard connected to the platform must not be disconnected until the second lanyard is attached to the structure.

The current owner, operator, and user is responsible for the safe and proper utilization of the subject MEWP. JLG Industries, Inc. assumes no responsibility or liability for any and all incidents involving personal injury, property damage, or equipment damage which may occur when transferring to a structure while elevated. Should you have any additional questions, please advise.

Sincerely,

JLG INDUSTRIES, INC.

Product Safety & Reliability Department

7/2024

JLG Industries, Inc.
Toll-free in US 877-JLG-LIFT
www.jlg.com

An Oshkosh Corporation Company