

JLG<sup>®</sup> Compact Crawler Series

# REACHINGOUT

Introducing the range of compact crawler boom lifts from JLG, specialists in off-slab and uneven terrain.

The JLG X-Series compact crawler boom lifts feature tracked wheel carriages that climb steps and a narrow chassis for access through gates, yards and doorways. Working heights range from 17m to 26m – Platform Capacities come with standard 230 kgs on all models, except for the X23J, which comes in dual capacities of 120/200 kgs.

JLG Compact Crawlers are low weight and can be operated via an engine as well as electrically. This makes them extremely versatile, whether working indoors or out.

YOUR MOBILE, LOW WEIGHT TOOL FOR OVERHEAD WORK







## **SPECIALIST DESIGN**

Whatever the task, JLG X-Series excel at multi-purpose application. JLG X-Series can go almost anywhere, the near square outrigger pattern helps provide additional stability, whilst the standard removable outrigger pads help minimize the impact to sensitive areas. The crawler carriage gives the X-Series its terrain ability, allowing it to climb grades up to 40%.

#### SPECIALIST DESIGN:

- Standard removable outrigger pads
- Extendable undercarriage
- Operating slope max. 11° (X23J up to 13°)
- Flexible positioning of outriggers (X23J)

#### TYPICAL AREAS OF APPLICATION:

- Gardening and landscaping
- Cleaning and maintenance
- Light construction
- Inspection and renovation work



**Gradeability**Operating slope max. 11°
(X23J up to 13°).



## **Specialist Design**

Standard removable outrigger pads and basket. Extendable undercarriage provides additional stability during transport.

## **EXCEPTIONAL FLEXIBILITY**

The JLG X-Series are equipped as standard with an electric motor, an ideal solution when working indoor – as no noise or emissions are created. The engine (choice petrol or diesel) is mounted at the rear, as far away from the operator as possible. Optional 'zero maintenance' lithium batteries are available.

Three models from the JLG X-Series – the X15J Plus, the X20J Plus and the X26J Plus – allow for 230kg platform capacity, increasing productivity by permitting to bring additional tools into the basket, without restricting the work envelope.



## Flexibility

Several engine options available. All crawlers are equipped as standard with AC electric motor (110V/220V). Optional lithium batteries available.



### **Model Range**

4 Models with standard 230 kgs of platform capacity (X15JP, X17JP, X20JP, X26JP) and 1 model with dual capacity of 120/200 kgs (X23J).



#### **X-Series Compact Crawler Boom Lifts X23J Dimensions** Working Height w 120 kg capacity 23.10 m Working Height w 200 kg capacity 21.70 m Horizontal Outreach 11.13 m (Std Platform w 120kg) Horizontal Outreach 9.75 m (Std Platform w 200kg) Platform size (standard 2 persons) 0.69 m x 1.30 m Stowed width (without platform) 0.99 m Stowed height (on tracks) 1.99 m Stowed length (on tracks) 6 m Outrigger footprint 3.98 m x 3.98 m Machine weight (with standard platform) 2,990 kg Operating weight (with petrol engine) 3,100 Kg 110V or 220V, 50Hz, 2.2kW AC electric motor Honda iGX440, Engine

11 kw Petrol

#### MAIN FEATURES

- Compact dimensions and low weight
- Low ground bearing pressure
- 361° noncontinuous swing
- Load sensing under the Platform
- Standard autostabilisation
- Working indoor and out

X-Series Compact Crawler Boom Lifts	X15J Plus	X17J Plus	X20J Plus	X26J Plus
Dimensions				
Working Height 230kg capacity	15.4 m	16.96 m	20.05 m	25.70 m
Horizontal Outreach (Std Platform 230kg)	6.1 m	7.00 m	9.20 m	13.20 m
Platform size (standard 2 persons)	0.69 X 1.34 m	0.69 m x 1.34 m	0.69 m x 1.34 m	0.69 m x 1.34 m
Stowed width (without platform)	0.748 m	0.798 m	0.795 m	0.990 m
Stowed height (on tracks)	1.99 m	2.00 m	1.99 m	1.98 m
Stowed length (on tracks, without platform)	4.02 m	4.53 m	5.00 m	5.98 m
Outrigger footprint	2.88 X 2.88 m	2.89 x 2.88 m	2.92 m x 2.93 m	4.08 m x 3.99 m
Machine weight (with standard platform)	1,910 kg	2,190 kg	2,840 kg	4,365 kg
Operating weight (with petrol engine)	1,940 kg	2,230 kg	2,880 kg	2,880 kg
AC electric motor	2.2 KW 50Hz 220V	2.2 KW 50Hz 230V	2.2 KW 50Hz 230V	2.2 KW 50Hz 230V
Engine	Honda iGX390 Hatz 1B40	Honda iGX440, 11 kw Petrol	Honda iGX440, w11 kw Petrol	Kubota D902-E3B

### ON PLUS MODELS

- Forklift pockets
- Anchor points on outriggers
- 230 kg unrestricted platform capacity

JLG Industries, Inc.

1 JLG Drive McConnellsburg, PA 17233-9533 Telephone 717-485-5161 Toll-free in US 877-JLG-LIFT Fax 717-485-6417

**Oshkosh-JLG (Tianjin) Equipment Technology Co., Ltd. Shanghai Branch** No. 465, Xiao Nan Road, Fengxian District

Shanghai 201401, China DID: 800 819 0050 400 613 0050 (Mobile)

JLG Industries, Inc. is a leading designer and manufacturer of access equipment and complementary services and attachments.

JLG has manufacturing facilities in the United States, France, Romania, China and Belgium. Customers throughout Europe, Africa and the Middle East benefit from a network of dedicated sales and service operations designed to deliver the highest levels of support.

www.jlg.com JLG is an Oshkosh Corporation company.

