# **460SJ HC3**

#### TELESCOPIC HI-CAPACITY BOOM LIFTS



#### **Performance**

Platform Height 14.05 m
Working Height 16.05 m
Horizontal Outreach 12.23 m
Swing 360 Degrees Continuous

Platform Capacity

Restricted 340/454 kg Unrestricted 300 kg

Platform Rotator 180 Degrees Hydraulic

Jib

Range of Articulation 1.83 m

130 Degrees (+70, -60)

Weight\* 9,250 kg
Max. Ground Bearing Pressure 6.96 kg/cm²
Drive Speed 6.8 km/h
Gradeability 45%
Tilt Cut Out 5 Degrees

Turning Radius

Outside 4.8 m Inside 2.07 m

## **Standard Specifications**

#### **Power Source**

Dual Fuel Engine
Deutz D2.9L4 Tier 4 Final 49 hp 36.4 kW

Fuel Tank Capacity 83.3 L

## **Hydraulic Reservoir**

Hydraulic Reservoir 136.27 LAuxiliary Power 12V-DC

### **Tyres**

• Standard 12 x 16.5 Foam Filled Non-marking

#### **Standard Features**

- 180 Degree Hydraulic Platform Rotator
- Platform Console Machine Status Light Panel\*
- 5 Degree Tilt Alarm/Indicator Light
- Swing Out Engine Tray
- 12V-DC Auxiliary Power
- Hourmeter
- Improved Multi-Function Controls
- Proportional Controls
- Interactive Display at Ground Controls
- Control ADE® System

- Lifting/Tie Down Lugs
- Horn
- Four-Wheel Hydrostatic Drive
- Inward Self-Closing Swing Gate
- Flashing Amber Beacon
- Operator Tool Tray
- Oscillating Axle
- Motion Alarm
- Glow Plugs (Diesel Engines)
- · Load Sensing System
- SkyGuard SkyLine™

\*Provides indicator lights at platform control console for system distress, low fuel, 4 degree tilt light, and foot switch status.



# **Accessories & Options**

- 36 x 72 in. (0.91 x 1.83 m) Platform
- 1/2 in. Air Line to Platform
- Pipe Racks
- White Noise (Squawker) Motion Alarm
- SkySense™
- SkyGlazier

- Light Package<sup>1</sup>
- Fire Extinguisher
- Battery Isolator
- Bolt on Fall Arrest
- Mesh to mid rail

Note: Some options may increase lead time, and some option combinations may not be available.

1. Includes platform work lights, head and tail lights, amber beacon.


# **460SJ HC3**


## TELESCOPIC HI-CAPACITY BOOM LIFTS




#### **Dimensions**

All dimensions are approximate.





## **Reach Diagrams**





# The JLG "1 & 5" Warranty

JLG Industries, Inc. backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/ or equipment changes without prior notification. This machine meets or exceeds AS/NZS 1418.10 2011 as originally manufactured for intended applications.

Regents Park, NSW 2143 Telephone 02 8718 6300 Fax 02 8718 6377

JLG Industries (Australia)

www.jlg.com.au

358 Park Road

**An Oshkosh Corporation Company**