

AM SERIES

PUSH-AROUND VERTICAL LIFT

JLG
reachingout®

Performance

Platform Height - Elevated

25AM	7.60 m
30AM	9.02 m
38AM	11.58 m

Platform Capacity

25AM	160 kg
30AM	135 kg
38AM	135 kg

Stowed Height

25AM	2.00 m
30AM	2.00 m
38AM	

Standard Position

2.64 m

Tilt Back Position

2.00 m

Base Length - Stowed

25AM	1.24 m
30AM	1.32 m
38AM	1.46 m

Overall Width - Stowed

25AM	0.74 m
30AM	0.74 m
38AM	0.74 m

Outrigger Footprint (LxW)

25AM	1.57 m x 1.38 m
30AM	1.90 m x 1.83 m
38AM	2.14 m x 2.18 m

Weight

25AM	AC 374 kg	DC 411 kg
30AM	AC 467 kg	DC 503 kg
38AM	AC 574 kg	DC 633 kg



Standard Features

- Low Maintenance Anodized Aluminum Mast
- Dual Chain Vertical Mast
- 4 Easy Fit Outriggers with Interlock Switch and Telltale Light Indicator
- 0.66 m x 0.66 m Platform with Drop Bar Entry Gate
- Non-Marking Solid Tyres
- 1 x 12V DC Deep Cycle Battery
- Removable SCR Battery Charger
- Battery Discharge Indicator at Base
- Transportation Tie Downs
- Built-In Fork Truck Pockets
- AS/NZS 1418.10 Compliant

Accessories & Options

- Fluorescent Light Tube Caddy
- Tool Tray (20 x 45 x 125 cm)
- AC Outlet to Platform

The JLG "1 & 5" Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.

JLG
reachingout®

JLG Industries (Australia)

358 Park Road
Regents Park, NSW 2143
Telephone 02 8718 6300
Fax 02 8718 6377
www.jlg.com.au

An Oshkosh Corporation Company