



WINCH

Single or Dual
8,000 lb.
winchLOCKLINK®

BODY

Modular aluminum construction, designed to provide years of service and ease

UNDERLIFT

Self-loading 4,000 lb. lift capacity with hydraulic L-arms that feature mechanical

SPECIFICATIONS

ENGINEERED FOR **STRENGTH AND DURABILITY**

The MPL-40 is Light Duty Integrated Wrecker is an 8 ton wrecker that features a 2-stage recovery boom, 4,000 lb. self-loading underlift, Underlift Level Stop System® and a modular aluminum body.

BECAUSE THE WORK **DEMANDS IT.**

Want a truck that works as hard as you do?

Visit our website at Jerrdan.com to find your nearest distributor.

RECOVERY BOOM: 2-STAGE

Retracted Capacity @ 30°	16,000 lbs.
Extended Capacity @ 30°	6,000 lbs.
Maximum Hook Height	110 in.
Maximum Boom Angle	32°

REACH PAST TAILBOARD

Reach Past Tailboard - Extended @ 0°	67 in.
Reach Past Tailboard - Extended @30°	46 in.

UNDERLIFT BOOM

Retracted Rating	4,000 lbs.
Retracted Reach	52 in.
Extended Rating	4,000 lbs.
Extended Reach	81 in.
Positive Tilt	20°
Negative Tilt	20°
Tow Capacity	7,500 lbs.

WINCH

Winch Capacity	8,000 lbs.
Winch Options	Single or Dual
Wire Rope (EIPS Galvanized)	3/8 in. x 110 ft. (Optional Swivel Hook)

CHASSIS

Minimum GVW Rating	11,000 lbs.
Minimum Cab-to-Axle, CA	60 in.

LIGHT DUTY WRECKER

INTEGRATED MPL-40

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Dual Side EH Controls	•	
Wired Winch Remote Control	•	
Wireless Underlift Remote Control*		•
Wired Underlift Remote Control		•
Wireless Full-Function Remote Control*		•
BODY		
No-Lube™ Technology	•	
Greaseable Joints w/ Grease Fittings		•
Lighted Toolboxes	•	
Polished Stainless Rails		•
Aluminum Deck Dress Up Kits*		•
24 in. Aluminum Tunnel Box		•
LIGHTING & ELECTRICAL		
7-way RV/4-Way Flat Trailer Connection	•	
DOT Lighting	•	
Backup Alarm	•	
Fold Down Light Bar Mount		•
In-Cab Switch Panel		•
LED Work Lights Upper - Pylon Mounted		•
LED Lightbar		•
Backup Camera Kit		•
Steel Tubular Light Pylon		•
BOOM & WINCHES		
8,000 lb. Boom w/ Dual Lift Cylinders	•	
Self-loading Wheel Grids w/ LOCKLINK®	•	
Underlift Level Stop Assist System	•	
Remote Free Spool Handles	•	
Single 8,000 lb. Work Gear Winch with Tensioner Plate and Free Spool	•	
Dual Work Gear Winches with Tensioner Plate and Free Spool		•
Tailboard D-rings Options		•

FEATURES	STANDARD	OPTIONAL
TOWING ACCESSORIES		
Wheel Lift Tie-Down Straps	•	
Fifth Wheel Plate*		•
Tow Sling & Mounting Brackets		•
Gooseneck Trailer Attachment*		•
Spade Foot Attachment		•
Low Angle Recovery Sheave w/ Hydraulic Tilt Lockout Valve		•
Motorcycle Attachment		•
Aluminum Dollies		•
Trailer Ball Attachments (available in sizes: 1-7/8 in., 2 in., 2-5/16 in.)*		•
Manual L-Arm Wheel Grids		•