

FULL  
COVERAGE  
**1**  
YEAR  
WARRANTY

+

STRUCTURAL  
COVERAGE  
**5**  
YEAR  
WARRANTY



### BODY

Modular aluminum construction, designed to provide years of service and ease of maintenance

### WINCH

Single 8,000 lbs. winch

### UNDERLIFT

Self-loading 4,000 lb. lift capacity with hydraulic L-arms that feature mechanical LOCKLINK® technology

## SPECIFICATIONS

### ENGINEERED FOR **STRENGTH AND DURABILITY**

The MPL-NG Light Duty Integrated Wrecker features a 4,000 lb. self-loading underlift, Underlift Level Stop System® and a modular aluminum body.

#### UNDERLIFT BOOM

Retracted Rating	4,000 lbs.
Retracted Reach	48 in.
Extended Rating	4,000 lbs.
Extended Reach	79 in.
Positive Tilt	15°
Negative Tilt	7°
Tow Capacity	7,500 lbs.

#### WINCH

Winch Capacity	8,000 lbs.
Winch Options	Single
Wire Rope (EIPS Galvanized)	3/8 in. x 75 ft. or 3/8 in. x 110 ft.

#### CHASSIS

Minimum GVW Rating	11,000 lbs.
Minimum Cab-to-Axle, CA	60 in.

BECAUSE THE  
WORK **DEMANDS** IT.

Want a truck that works as hard as you do?

Visit our website at [Jerrdan.com](http://Jerrdan.com) to find your nearest distributor.

# LIGHT DUTY WRECKER

## INTEGRATED MPL-NG

FEATURES	STANDARD	OPTIONAL
<b>CONTROLS</b>		
Wired Winch Remote Control	•	
Wireless Winch Remote Control		•
<b>BODY</b>		
No-Lube™ Technology	•	
Greaseable Joints w/ Grease Fittings		•
Lighted Toolboxes	•	
Polished Stainless Rails		•
Aluminum Deck Dress Up Kits*		•
24 in. Aluminum Tunnel Box		•
<b>LIGHTING &amp; ELECTRICAL</b>		
7-way RV/4-Way Flat Trailer Connection	•	
DOT Lighting	•	
Backup Alarm	•	
Fold Down Light Bar Mount		•
In-Cab Switch Panel		•
LED Work Lights Upper - Pylon Mounted		•
LED Lightbar		•
Backup Camera Kit		•
Steel Tubular Light Pylon	•	
<b>WINCH</b>		
Single 8,000 lb. Worm Gear Winch with Wire Tensioner Plate and Free Spool		•
Remote Free Spool Handles	•	
Tailboard D-rings Options		•
<b>UNDERLIFT</b>		
Underlift Level Stop Assist System	•	
Self-loading Wheel Grids w/ LOCKLINK® Technology	•	

FEATURES	STANDARD	OPTIONAL
<b>TOWING ACCESSORIES</b>		
Wheel Lift Tie-Down Straps	•	
Fifth Wheel Plate*		•
Gooseneck Trailer Attachment*		•
Low Angle Recovery Sheave w/ Hydraulic Tilt Lockout Valve		•
Motorcycle Attachment		•
Self-Loading Aluminum Dollies		•
Trailer Ball Attachments (available in sizes: 1-7/8 in., 2 in., 2-5/16 in.)*		•
Manual L-Arm Wheel Grids		•

\*Available through parts only