



### DECK

Built to be tough and reliable. Aluminum and Steel construction. 17,000 lbs. structural capacity.

### WHEEL LIFT

Low profile and versatile. Various grid options available. 3,500 lbs. or 5,000 lbs. lift capacities.

### WINCH

Up to 12,000 lbs. capacity winches for maximum pulling power.

## SPECIFICATIONS

### A MULTIPURPOSE WORKHORSE THAT WON'T LET YOU DOWN

The 8.5 Ton XLP Carrier is available in steel or aluminum, with multiple deck length and width configurations and a 17,000-lbs. structural deck capacity for more strength and durability on the job.

BECAUSE THE WORK DEMANDS IT.

Want a truck that works as hard as you do?

Visit our website at [Jerrdan.com](http://Jerrdan.com) to find your nearest distributor.

#### CARRIER DECK

Capacity	17,000 lbs.
Deck Width	96 in., 102 in.
Deck Length	22 ft., 24 ft., 26 ft., 28 ft., 30 ft.
Material Type	Steel or Aluminum

#### WHEEL LIFT

##### 3,500 LBS. WHEEL LIFT

Lift Capacity	3,500 lbs.
Tow Capacity	10,000 lbs.
Maximum Extended Reach from Tail to Bed	65 in.

##### 5,000 LBS. WHEEL LIFT

Lift Capacity	5,000 lbs.
Tow Capacity	12,000 lbs.
Maximum Extended Reach from Tail to Bed	67 in.

#### WINCH

Winch Capacity	Single 10,000 lbs. or 12,000 lbs. Dual 8,000 lbs.
----------------	--

#### CHASSIS

Minimum GVWR (W/o wheel lift)	25,500 lbs.
Minimum GVWR (W/ wheel lift)	33,000 lbs.
Cab to Axle (CA) Range	138 in.-150 in. (22 ft. deck) 156 in.-168 in. (24 ft. deck) 180 in.-192 in. (26 ft. deck) 204 in.-214 in. (28 ft. deck) 228 in.-238 in. (30 ft. deck)

# MEDIUM DUTY CARRIER

## 8.5 TON XLP

FEATURES	STANDARD	OPTIONAL
<b>CONTROLS</b>		
Dual Lighted Side Controls	•	
Wireless Remote (Up to 5 functions)		•
<b>DECK &amp; SUBFRAME</b>		
<b>STEEL</b>		
Single Sheet 3/16 in. Diamond or Smooth Decking	•	
5 in. Removable Tubular Steel Rails		•
5 in. Polished Aluminum Blade Rails		•
<b>ALUMINUM</b>		
High Strength Extruded Aluminum	•	
Patented Galvanized Steel Main Beams	•	
5 in. Fixed Blade Rails (NGAF)		•
<b>STEEL &amp; ALUMINUM</b>		
Center Mounted Hydraulic Valve	•	
12 Keyslots	•	
Hydraulic Pressure Gauge	•	
Hose & Wiring Track System	•	
Outboard Tilt Cylinders	•	
Headboard - Deck Mounted or Stationary Frame Mounted	•	
Side Recovery System (SRS)		•
Galvanized Subframe & Wheel Lift		•
102 in. Deck Width		•
<b>LIGHTING &amp; ELECTRICAL</b>		
LED Lighting	•	
LED Work Lights		•
Rear Awareness Indicator Lights (RAIL)		•

FEATURES	STANDARD	OPTIONAL
<b>TOWING ACCESSORIES</b>		
Wheel Lift Grids (Manual)		•
Camlocks ILO of T-Handle (Manual Grids)		•
Reese Receiver ILO of Ball Hitch Mounting Plate (Manual Grids)		•
Hydraulic Rear Dock Stabilizer (Various trailer towing provisions available)		•
*Option available when wheel lift is deleted		
<b>ACCESSORIES</b>		
Toolbox (36 in., 48 in. or 60 in.)		•
Toolbox Trays		•
<b>WINCH &amp; WIRE ROPE</b>		
10,000 lbs. Worm Gear Winch w/ 7/16 in. x 56 ft. EIPS Galvanized Wire Rope		•
12,000 lbs. Worm Gear w/ 7/16 in. x 56 ft. EIPS Galvanized Wire Rope (Only available w/ single manual free spool)		•
10,000 lbs. Sliding Planetary Winch w/ 7/16 in. x 56 ft. EIPS Galvanized Wire Rope		•
Dual 8,000 lbs. Worm Gear Winches w/ 3/8 in. x 56 ft. EIPS Galvanized Wire Rope (Only available on 28 ft. & 30 ft.)		•
Dual Side Manual Free Spool (10,000 lbs. Winch only)		•
Air Controlled Winch Free Spool (10,000 lbs. Winch only)		•

V0824