



DECK

Built to be tough and reliable. Aluminum upper deck (5,000 lbs. structural capacity). Aluminum and Steel construction main deck (17,000 lbs. structural capacity).

WINCH

8,000 lbs. upper deck winch. Dual 8,000 lbs. main deck winches.

WHEEL LIFT

Low profile and versatile. Various grid options available. 3,500 lbs. or 5,000 lbs. lift capacities.

SPECIFICATIONS

A MULTIPURPOSE WORKHORSE THAT WON'T LET YOU DOWN

The 8.5 Ton XLP Multi-Car Carrier features a 5,000 lbs. upper deck structural capacity and a 8,000 lbs. winch, while the lower deck has a 17,000 lbs. structural capacity and two 8,000 lbs. winches.

BECAUSE THE WORK DEMANDS IT.

Want a truck that works as hard as you do?

Visit our website at Jerrdan.com to find your nearest distributor.

CARRIER DECK

Capacity (upper deck)	5,000 lbs.
Capacity (lower deck)	17,000 lbs.
Deck Width	96 in., 102 in.
Upper Deck Length	14 ft.
Lower Deck Length	28 ft., 30 ft.
Material Type	Steel or Aluminum

WHEEL LIFT

3,500 LBS. WHEEL LIFT

Lift Capacity	3,500 lbs.
Tow Capacity	10,000 lbs.
Maximum Extended Reach from Tail to Bed	64 in.

5,000 LBS. WHEEL LIFT

Lift Capacity	5,000 lbs.
Tow Capacity	12,000 lbs.
Maximum Extended Reach from Tail to Bed	66 in.

WINCH

Winch Capacity	Single 8,000 lbs. (Upper deck) Dual 8,000 lbs. (Lower deck)
----------------	--

CHASSIS

Minimum GVWR (w/ wheel lift)	33,000 lbs.
Cab to Axle (CA) Range	208 in.-214 in. (28 ft. lower deck), 232 in.-238 in. (30 ft. lower deck)
Cab to Tandem (CT) Range	186 in.-192 in. (28 ft. lower deck), 210 in.-216 in. (30 ft. lower deck)

MEDIUM DUTY CARRIER

8.5 TON XLP MULTI-CAR

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Dual Lighted Side Controls	•	
Wireless Remote (Up to 5 functions)		•
DECK & SUBFRAME		
STEEL		
Single Sheet 3/16 in. Diamond or Smooth Decking	•	
5 in. Removable Tubular Steel Rails		•
5 in. Polished Aluminum Blade Rails		•
ALUMINUM		
High Strength Extruded Aluminum	•	
Patented Galvanized Steel Main Beams	•	
5 in. Fixed Blade Rails (NGAF)		•
STEEL & ALUMINUM		
Center Mounted Hydraulic Valve	•	
14 Keyslots (Lower deck)	•	
4 Keyslots, 2 D-ring Keyslots, 2 Ratchet Binders (Upper deck)	•	
Hydraulic Pressure Gauge	•	
Hose & Wiring Track System	•	
Outboard Tilt Cylinders	•	
Headboard - Deck Mounted or Stationary Frame Mounted	•	
Galvanized Subframe & Wheel Lift		•
102 in. Deck Width (Lower deck only)		•
LIGHTING & ELECTRICAL		
LED Lighting	•	
LED Work Lights (Rear support, Top deck winch, Rear lower subframe)	•	
Rear Awareness Indicator Lights (RAIL)		•

FEATURES	STANDARD	OPTIONAL
TOWING ACCESSORIES		
Wheel Lift Grids (Manual)		•
Camlocks ILO of T-Handle (Manual Grids)		•
Reese Receiver ILO of Ball Hitch Mounting Plate (Manual Grids)		•
Hydraulic Rear Dock Stabilizer (Various trailer towing provisions available)		•
*Option available when wheel lift is deleted		
ACCESSORIES		
Toolbox (36 in., 48 in. or 60 in.)		•
Toolbox Trays		•
WINCH & WIRE ROPE		
Dual 8,000 lbs. Worm Gear Winches w/ 3/8 in. x 56 ft. EIPS Galvanized Wire Rope (Lower deck)	•	
Single 8,000 lbs. Worm Gear Winch w/ 3/8 in. x 75 ft. EIPS Galvanized Wire Rope (Upper deck)	•	
Driver Side Manual Free Spool (Lower deck)	•	
Air Controlled Winch Free Spool (Upper deck)	•	

V0824