



WINCH

Single 8,000 lbs. winch

BODY

Steel welded body for value-added durability

UNDERLIFT

Self-loading 4,000 lbs. lift capacity with hydraulic L-arms that feature mechanical LOCKLINK® technology

SPECIFICATIONS

ENGINEERED FOR STRENGTH AND DURABILITY

The MPL-NG Light Duty Integrated Wrecker features a 4,000 lbs. self-loading underlift with an automatic boom Level Stop Assist System®, and a steel welded body.

UNDERLIFT BOOM

Retracted Rating	4,000 lbs.
Retracted Reach	48 in.
Extended Rating	4,000 lbs.
Extended Reach	79 in.
Positive Tilt	15°
Negative Tilt	7°
Tow Capacity	7,500 lbs.

WINCH

Winch Capacity	8,000 lbs.
Winch Options	Single
Wire Rope (EIPS Galvanized)	3/8 in. x 75 ft. or 3/8 in. x 110 ft.

CHASSIS

Minimum GVW Rating	11,000 lbs.
Minimum Cab-to-Axle, CA	60 in.

BECAUSE THE WORK DEMANDS IT.

Want a truck that works as hard as you do?

Visit our website at Jerrdan.com to find your nearest distributor.

LIGHT DUTY WRECKER

INTEGRATED MPL-NG

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Wired Winch Remote Control	•	
Wireless Winch Remote Control		•
BODY		
No-Lube™ Technology	•	
Greaseable Joints w/ Grease Fittings		•
Lighted Toolboxes	•	
Polished Stainless Rails		•
Aluminum Deck Dress Up Kits*		•
24 in. Aluminum Tunnel Box		•
LIGHTING & ELECTRICAL		
7-Way RV/4-Way Flat Trailer Connection	•	
DOT Lighting	•	
Backup Alarm	•	
Fold Down Light Bar Mount		•
In-Cab Switch Panel		•
LED Work Lights Upper - Pylon Mounted		•
LED Lightbar		•
Backup Camera Kit		•
Steel Tubular Light Pylon	•	
WINCH		
Single 8,000 lbs. Worm Gear Winch with Wire Tensioner Plate and Free Spool		•
Remote Free Spool Handles	•	
Tailboard D-Ring Options		•
UNDERLIFT		
Underlift Level Stop Assist System	•	
Self-loading Wheel Grids w/ LOCKLINK® Technology	•	

FEATURES	STANDARD	OPTIONAL
TOWING ACCESSORIES		
Wheel Lift Tie-Down Straps	•	
Fifth Wheel Plate*		•
Gooseneck Trailer Attachment*		•
Low Angle Recovery Sheave w/ Hydraulic Tilt Lockout Valve		•
Motorcycle Attachment		•
Self-Loading Aluminum Dollies		•
Trailer Ball Attachments (available in sizes: 1-7/8 in., 2 in., 2-5/6 in.)*		•
Manual L-Arm Wheel Grids		•

* Available through parts only

V0824