

FULL
COVERAGE
1
YEAR
WARRANTY

STRUCTURAL
COVERAGE
5
YEAR
WARRANTY

WINCH

Single 8,000 lbs. winch

UNDERLIFT

Self-loading 4,000 lbs. lift capacity with hydraulic L-arms that feature mechanical LOCKLINK® technology

BODY

Steel welded body for value-added durability

SPECIFICATIONS

ENGINEERED FOR STRENGTH AND DURABILITY

The MPL-NGs Light Duty Integrated Wrecker features a 4,000 lbs. self-loading underlift with an automatic boom Level Stop Assist System®, and a steel welded body.

UNDERLIFT BOOM

| | |
|------------------|------------|
| Retracted Rating | 4,000 lbs. |
| Retracted Reach | 48 in. |
| Extended Rating | 4,000 lbs. |
| Extended Reach | 79 in. |
| Positive Tilt | 15° |
| Negative Tilt | 7° |
| Tow Capacity | 7,500 lbs. |

WINCH

| | |
|-----------------------------|---------------------------------------|
| Winch Capacity | 8,000 lbs. |
| Winch Options | Single |
| Wire Rope (EIPS Galvanized) | 3/8 in. x 75 ft. or 3/8 in. x 110 ft. |

CHASSIS

| | |
|-------------------------|-------------|
| Minimum GVW Rating | 11,000 lbs. |
| Minimum Cab-to-Axle, CA | 60 in. |

LIGHT DUTY WRECKER

INTEGRATED MPL-NGS

| FEATURES | STANDARD | OPTIONAL |
|--|----------|----------|
| CONTROLS | | |
| Wired Control w/o Winch | • | |
| Wired Control w/ Winch | | • |
| Wireless w/o Winch | | • |
| Wireless w/ Winch | | • |
| BODY | | |
| Steel Welded Body with Diamond Plate Decking | • | |
| No-Lube™ Technology | • | |
| Greasable Joints w/ Grease Fittings | | • |
| Aluminum Tunnels | | • |
| Driver Side Toolbox | • | |
| Passenger Side Tool | • | |
| LIGHTING & ELECTRICAL | | |
| DOT Lighting | • | |
| Backup Alarm | • | |
| Fold Down Light Bar Mount | | • |
| In-Cab Switch Panel | | • |
| LED Work Lights Upper - Pylon Mounted | | • |
| LED Lightbar | | • |
| Backup Camera Kit | | • |
| Steel Tubular Light Pylon | | • |
| WINCH | | |
| Single 8,000 lbs. Worm Gear Winch with Wire Tensioner Plate and Free Spool | | • |
| Tailboard D-Ring Options | | • |
| UNDERLIFT | | |
| Underlift Level Stop Assist System | • | |
| Self-loading Wheel Grids w/ LOCKLINK® Technology | • | |

| FEATURES | STANDARD | OPTIONAL |
|---|----------|----------|
| TOWING ACCESSORIES | | |
| Wheel Lift Tie-Down Straps | • | |
| Fifth Wheel Plate | | • |
| Gooseneck Trailer Attachment | | • |
| Motorcycle Attachment | | • |
| Low Angle Recovery Sheave w/ Hydraulic Tilt Lockout Valve | | • |
| Self-Loading Aluminum Dollies | | • |
| Trailer Ball Attachments (available in sizes: 1-7/8 in., 2 in., 2-5/6 in.)* | | • |
| Manual L-Arm Wheel Grids | | • |

*Available through parts only

V0824