



### DECK

Built to be tough and reliable. Aluminum upper deck (5,000 lb. structural capacity). Aluminum and Steel construction main deck (17,000 lb. structural capacity).

### WINCH

8,000 lb. upper deck winch. Dual 8,000 lb. main deck winches.

### BODY

Low profile and versatile. Various grid options available. 3,500 lb. or 5,000 lbs. lift capacities.

## SPECIFICATIONS

### A MULTIPURPOSE WORKHORSE THAT WON'T LET YOU DOWN

The 8.5 Ton XLP Multi-Car Carrier features a 5,000 lb. upper deck structural capacity and a 8,000 lb. winch, while the lower deck has a 17,000 lb. structural capacity and two 8,000 lb. winches.

BECAUSE THE WORK **DEMANDS** IT.

Want a truck that works as hard as you do?

Visit our website at [Jerrdan.com](http://Jerrdan.com) to find your nearest distributor.

### CARRIER DECK

Capacity (upper deck)	5,000 lbs.
Capacity (lower deck)	17,000 lbs.
Deck Width	96 in., 102 in.
Upper Deck Length	14 ft.
Lower Deck Length	28 ft., 30 ft.
Material Type	Steel or Aluminum

### WHEEL LIFT

#### 3,500 LB. WHEEL LIFT

Lift Capacity	3,500 lbs.
Tow Capacity	10,000 lbs.
Maximum Extended Reach from Tail to Bed	64 in.

#### 5,000 LB. WHEEL LIFT

Lift Capacity	5,000 lbs.
Tow Capacity	12,000 lbs.
Maximum Extended Reach from Tail to Bed	66 in.

### WINCH

Winch Capacity	Single 8,000 lb (Upper deck) Dual 8,000 lb (Lower deck)
----------------	--

### CHASSIS

Minimum GVWR (w/ wheel lift)	33,000 lbs.
Cab to Axle (CA) Range	208 in.-214 in. (28 ft. lower deck), 232 in.-238 in. (30 ft. lower deck)
Cab to Tandem (CT) Range	186 in. -192 in. (28 ft. lower deck), 210 in.-216 in. (30 ft. lower deck)

# MEDIUM DUTY CARRIER

## 8.5 TON XLP MULTI-CAR

FEATURES	STANDARD	OPTIONAL
<b>CONTROLS</b>		
Dual Lighted Side Controls	•	
Wireless Remote (Up to 5 functions)		•
<b>DECK &amp; SUBFRAME</b>		
<b>STEEL</b>		
Single Sheet 3/16 in. Diamond or Smooth Decking	•	
5 in. Removable Tubular Steel Rails		•
5 in. Polished Aluminum Blade Rails		•
<b>ALUMINUM</b>		
High Strength Extruded Aluminum	•	
Patented Galvanized Steel Main Beams	•	
5 in. Fixed Blade Rails (NGAF)		•
<b>STEEL &amp; ALUMINUM</b>		
Center Mounted Hydraulic Valve	•	
14 Keyslots (Lower deck)	•	
4 Keyslots, 2 D-ring Keyslots, 2 Ratchet Binders (Upper deck)	•	
Hydraulic Pressure Gauge	•	
Hose & Wiring Track System	•	
Outboard Tilt Cylinders	•	
Headboard - Deck Mounted or Stationary Frame Mounted	•	
Galvanized Subframe & Wheel Lift		•
102 in. Deck Width (Lower deck only)		•
<b>LIGHTING &amp; ELECTRICAL</b>		
LED Lighting	•	
LED Work Lights (Rear support, Top deck winch, Rear lower subframe)	•	
Rear Awareness Indicator Lights (RAIL)		•

FEATURES	STANDARD	OPTIONAL
<b>TOWING ACCESSORIES</b>		
Wheel Lift Grids (Manual)		•
Camlocks ILO of T-Handle (Manual Grids)		•
Reese Receiver ILO of Ball Hitch Mounting Plate (Manual Grids)		•
Hydraulic Rear Dock Stabilizer (Various trailer towing provisions available)		•
*Option available when wheel lift is deleted		
<b>ACCESSORIES</b>		
Toolbox (36 in., 48 in. or 60 in.)		•
Toolbox Trays		•
<b>WINCH &amp; WIRE ROPE</b>		
Dual 8,000 lb. Worm Gear Winches w/ 3/8 in. x 56 ft. EIPS Galvanized Wire Rope (Lower deck)	•	
Single 8,000 lb. Worm Gear Winch w/ 3/8 in. x 75 ft. EIPS Galvanized Wire Rope (Upper deck)	•	
Driver Side Manual Free Spool (Lower deck)	•	
Air Controlled Winch Free Spool (Upper deck)	•	