

BOOM


70,000 lb. capacity retracted

UNDERLIFT

Optional 3-stage or 4-stage independent underlift with knee booms

BODY

Built with a polypropylene copolymer material that is high-impact resistant and corrosion-free



SPECIFICATIONS

BUILT FOR STRENGTH, RELIABILITY AND DURABILITY

The JD35 Heavy Duty Independent Wrecker features a 70,000 lb. 2-stage wrecker boom, corrosion-resistant body and optional 3- or 4-stage underlifts – all designed with strength and performance in mind.

BECAUSE THE
WORK DEMANDS IT.

Want a truck that works as hard as you do?

Visit our website at Jerrdan.com to find your nearest distributor.

RECOVERY BOOM	
2-STAGE STANDARD	
Rated Capacity @ 30° Retracted	70,000 lbs.
Rated Capacity @ 30° Extended	22,000 lbs.
REACH PAST TAILBOARD	
Extended @ 0°	132 in.
Extended @ 30°	87 in.
OPERATING RANGE	
Maximum Boom Angle	39°
Maximum Hook Height	225 in.
WINCHES & WIRE ROPE	
Rated Capacity - Dual Boom Mounted Planetary Winches	35,000 lbs. each
Rated Working Load Limit - 5/8 in. x 250 ft. EIPS Galvanized	11,700 lbs. each
Rated Working Load Limit - 3/4 in x 200 ft. EIPS Galvanized	16,800 lbs. each
UNDERLIFT DRAG WINCH	
Rated Capacity - Single Underlift Mounted Planetary Winch	35,000 lbs.
Wire Rope 5/8 in. x 250 ft. EIPS Galvanized	11,700 lbs.
Wire Rope 3/4 in. x 200 ft. EIPS Galvanized	16,800 lbs.
KNEE BOOM UNDERLIFT	
350	
Rated Capacity - Retracted	35,000 lbs.
Rated Capacity - Extended	16,000 lbs.
Reach Past Tailboard - Retracted with Forks at Ground Level	64 in.
Reach Past Tailboard - Extended with Forks at Ground Level	128 in.
Positive Tilt	20°
Negative Tilt	18°
Tow Capacity	80,000 lbs.

HEAVY DUTY WRECKER

INDEPENDENT JD35

SPECIFICATIONS

KNEE BOOM UNDERLIFT

350X

Rated Capacity - Retracted	35,000 lbs.
Rated Capacity - Extended	16,000 lbs.
Reach Past Tailboard - Retracted with Forks at Ground Level	70 in.
Reach Past Tailboard - Extended with Forks at Ground Level	147 in.
Positive Tilt	20°
Negative Tilt	18°
Tow Capacity	80,000 lbs.

530

Rated Capacity - Retracted	53,000 lbs.
Rated Capacity - Extended	17,000 lbs.
Reach Past Tailboard - Retracted with Forks at Ground Level	72 in.
Reach Past Tailboard - Extended with Forks at Ground Level	142 in.
Positive Tilt	12°
Negative Tilt	18°
Tow Capacity	80,000 lbs.

565

Rated Capacity - Retracted	56,500 lbs.
Rated Capacity - Extended	17,600 lbs.
Reach Past Tailboard - Retracted with Forks at Ground Level	86 in.
Reach Past Tailboard - Extended with Forks at Ground Level	180 in.
Positive Tilt	13°
Negative Tilt	17°
Tow Capacity	80,000 lbs.

565 (4-STAGE)

Rated Capacity - Retracted	56,500 lbs.
Rated Capacity - Extended	17,600 lbs.
Reach Past Tailboard - Retracted with Forks at Ground Level	78 in.
Reach Past Tailboard - Extended with Forks at Ground Level	179 in.
Positive Tilt	15°
Negative Tilt	15°
Tow Capacity	80,000 lbs.

CHASSIS RECOMMENDATION

Minimum GVW Rating	54,000 lbs.
Minimum RBM Per Rail	3,250,000 in.-lbs.

HEAVY DUTY WRECKER

INDEPENDENT JD35

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Passenger Side Manual Controls with Passenger Side Hydraulic Pressure Gauges	•	
Driver Side Manual Controls	•	
Driver Side Hydraulic Gauge		•
Color Coded Winch Control Handles	•	
Color Coded Winch Sheave Guides and Hooks		•
Hydraulic Tank with Fluid Level Sight Gauge & Return Filter with Life Indicator	•	
Non-Proportional Underlift Remote	•	
Non-Proportional Boom/Winch/Underlift Remote		•
Proportional Boom/Winch Remote		•
Touchlink In-Cab Underlift Controls		•
BODY		
Structural Polypropylene Copolymer Body	•	
Anti-Skid Diamond Plate Walking Surface	•	
Painted Roll-Up Doors w/Satin Finish Door Frames	•	
Forward Facing Diamond Plate on Tunnel Box		•
Painted Roll-up doors w/ Painted Door Frames		•
Storage Solutions for Tools and Equipment		•
LIGHTING & ELECTRICAL		
Integrated Electronic Distribution System	•	
Touchlink Control System for Lighting and Winches with Integrated E-stop	•	
Interior Tool Box Lighting (LED)	•	
Clear Body Marker Lights (LED)	•	
Lighted Steps & Grab Handle (LED)	•	
Upper Hook-Up Lights (LED)		•
Lower Hook-Up Lights (LED)		•
Upper Work Lights- Pylon Mounted (LED)		•
Underlift Hook-Up Light (LED)		•
Underboom Light (LED)		•
Hood Mounted Flashers		•
Grille Mounted Flashers		•
Body Mounted Flashers		•
Main Light Bar		•
Wing Light Bars		•

FEATURES	STANDARD	OPTIONAL
BOOM, UNDERLIFT & WINCHES		
2- Stage Recovery Boom	•	
Boom Mounted D-Rings	•	
Hydraulic Rear Spades w/Flip Down Spade Foot	•	
350 Underlift w/ Knee Boom	•	
350X Underlift w/ Knee Boom		•
530 Underlift w/ Knee Boom (HDUL)		•
565 (3- or 4- stage) Underlift w/ Knee Boom (HDUL)		•
5 in. Crossbar Pivot Pin	•	
Integrated Safety Chain Storage	•	
Dual Planetary 2-Speed Winches	•	
Single Planetary 2-Speed Underlift Drag Winch		•
Air Free Spool w/ Adjustable Rope Tensioner	•	
Winch Camera with Control Station Monitors		•
TOWING ACCESSORIES		
7-Way Trailer Plug	•	
Recessed Glad Hands	•	
Service Air Quick Connect	•	
5 Sets of Lifting Forks	•	
Chain End Caps	•	
Backup Camera	•	
Rear Facing Underlift Camera		•
High Rise Fork Receivers		•
Bus Arms/Tire Lifts		•
5th Wheel Attachment		•
Pintle Hitch Attachment		•
Rigging Kits		•
Tunnel Box Counterweight Options		•
ACCESSORIES		
Side Recovery System (25,000 lb. Winch or 35,000 lb. Winch)		•
Side Stabilization System (SS-70- No winch)		•
Stainless Steel Rubrail Dress Up Kit		•
Stainless Steel Pylon Dress Up Kit		•